Technical Data Sheet

Divinol Spezialöl HGB V-R 10W-30

Product description

Divinol Spezialöl HGB V-R 10W-30 is a gear and hydraulic oil (UTTO), which can be used for tractors, agricultural machines and construction engines. The product guarantees an optimal frictional properties and reduces noise in wet brakes. The product offers excellent low-temperature performance as well as gear lubrication.

Specification

API GL-4/GL-5 low torque application

Manufacturer performance

Allison C-4; Case MS 1204/1206/1207/1209; Caterpillar TO-2; CNH MAT 3525/3526; Deutz-Allis AC Power Fluid 821 XL; IHC B5&B6 Hydran; Kubota UDT Fluid; Ford New Holland M2C41B/M2C48-C3/M2C86-B/M2C-134D, FNHA-2C-200.00/ 201.00; John Deere JDM J20 C/D; MF CMS M 1135/1141/1143/1145; New Holland NH410B/ NH420A/ 82948718; Volvo VME WB 101; Denison/Parker HF-0/HF-02; Eaton I-280-S/ M2950S; JCMAS HK P-041; White Q-1705/1722/1766/1766B/1802/1826; Oliver Type 55/5J/Q1802; Sauer/Danfoss Hydro Static Trans Fluid

Characteristics

SAE Grade:	10W-30 / SAE 80
Colour / DIN ISO 2049:	L 2,0
Viscosity/40°C / DIN 51 562:	70 mm²/s
Viscosity/100°C / DIN 51 562:	11.5 mm²/s
Viscosity index / DIN ISO 2909:	170
Density/15°C / DIN 51 757:	885 kg/m³
Pour point / DIN ISO 3016:	-35 °C
Flash point (Cleveland) / DIN ISO 2592:	210°C

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

Zeller+Gmelin
Mineralöle · Druckfarben · Chemie

ZG Division: Divinol Lubricants & Release Agents
Zeller+Gmelin GmbH & Co. KG
Schlossstr. 20 - 73054 Eislingen/Fils
Tel. +49 7161 802-0 - Fax +49 7161 802-230
www.zeller-gmelin.de - dst@zeller-gmelin.de

Technical Data Sheet

Divinol Spezialöl HGB V-R 10W-30

Application

Divinol Spezialöl HGB V-R 10W-30 is a gear and hydraulic oil (UTTO), which can be used for tractors, agricultural and construction machines.

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

Zeller+Gmelin
Mineralöle · Druckfarben · Chemie

ZG Division: Divinol Lubricants & Release Agents
Zeller+Gmelin GmbH & Co. KG
Schlossstr. 20 - 73054 Eislingen/Fils
Tel. +49 7161 802-0 - Fax +49 7161 802-230
www.zeller-gmelin.de - dst@zeller-gmelin.de