

Technical Data Sheet

Divinol Syntholight CC 0W-30

Product description

Divinol Syntholight CC 0W-30 is a smooth-running engine oil blended with most advanced HC synthesis technology oils and modern additives. It is recommended for Otto- and Diesel-engines, which need an engine oil according ACEA A5/B5, this oftentimes fits for Volvo Cars .

Specification

API SL; ACEA A5-10/B5-10

Manufacturer performance

Volvo Cars

Characteristics

SAE Grade:	0W-30
Viscosity/40°C / DIN 51 562:	57 mm ² /s
Viscosity/100°C / DIN 51 562:	10.5 mm ² /s
Viscosity index / DIN ISO 2909:	175
Density/15°C / DIN 51 757:	0,850 g/cm ³
Pour point / DIN ISO 3016:	-38 °C
Flash point (Cleveland) / DIN ISO 2592:	215 °C

Application

Divinol Syntholight CC 0W-30 guarantees a rapid oiling of the the engine even under low temperature conditions and offers a sufficiently thick lubricating film at higher temperatures.

49500

05/2014-49500-0

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 1