

Technical Data Sheet

Divinol Öl-Ex 82

Product description

Divinol Öl-Ex 82 is a new multipurpose oil and chemical absorbing agent - Type I, Type II and III R, which can be universally used in industry and commerce, on roads and other trafficked areas as well as on water. Grained, non-dusting material based on polyurethane (grain size 0.5-4 mm) to absorb only liquids (not the water) such as oil, drilling emulsions, paints, acids, alkalis, etc...

Environmental Impact:

The Federal Environment Ministry of Germany published "Requirements for oil binders" are fully met. The product is officially tested and approved under Certificate No. 75 015/05 dated 31.05.2005.

- chemically neutral
- very good stability, even oil-saturated non-slip
- not made of fiber structure but leaves

Application

Divinol Öl-Ex 82 is dispersed with a layer thickness of up to 3 mm and swept up with a broom after absorption. Old, oil-contaminated soil is firstly treated with solvent and then with Divinol Öl-Ex 82. The content of the bag (10 kg corresponds to 40 l) binds approximately 23 liters of fuel oil.

Disposal notice

Due to the fact that Divinol Öl-Ex 82 won't absorb water, there is no expensive disposal of e.g. a water-oil mixture, but only of the absorbed chemical. Divinol Öl-Ex 82 is ideal for thermal-energy recovery use and mustn't be disposed necessarily. Thus, valuable energy is saved and serves as combustible material. Divinol Öl-Ex 82 burns oil-soaked nearly residue-free with a minimum ash content of 2%.

67482

02/2013-67482-3

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 1